

DD10001

ISSUE	ITEM	CHANGED FROM	DATE	CN. NO.	DRAFTS	CHECKER	ENG. APP.	REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL
0		ORIGINAL RELEASE	2808/65		AM							

PEAK REVERSE VOLTAGE VOLTS	2000	TRANSIENT PEAK REVERSE VOLTAGE VOLTS	2500	MAX. AVER. FORWARD CURRENT AMPS	0.55	RECURRENT PEAK FORWARD CURRENT AMPS	5	SINGLE SURGE CURRENT AMPS	30	TEMP. °C	150	Vf at If VOLTS AMPS	0.55 0.55	Irev at PRV	10uA Max.	Mfgrs P/N	PH 103
----------------------------	------	--------------------------------------	------	---------------------------------	------	-------------------------------------	---	---------------------------	----	----------	-----	---------------------	-----------	-------------	-----------	-----------	--------

PS-7A	MODEL	PROJECT NO.	024/65	ASS'Y. NO.	DATE	STOCK SIZE	TMC (Canada) LIMITED OTTAWA ONTARIO
USED ON							
MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES				IF IT IS FOUND DESIRABLE TO CHANGE ANY TOLERANCE OR OTHER DETAIL SPECIFIED ON THIS DRAWING NOTIFY THE PURCHASER PROMPTLY.			
TOLERANCES				SCALE			
DEC. DIM. ±				DIMENSIONS IN INCHES			
FRAC. DIM. ±				UNLESS OTHERWISE SPECIFIED			
ANGULAR DIM. ±				DRILL, PUNCH, COMMERCIAL STOCK SIZES AND MANUFACTURERS TOLERANCES ARE NOT INCLUDED.			
ALL OTHERS	S10045-31			HEAT TREAT. SPEC.			
FINISH & SPEC. NO.				DRAWN			
ELEC. DES. APP.				MECH. DES. APP.			
DRAWN				CHECKED			
FINAL APPROVAL				PH			
DD10001				Φ			