



DL 10008

ISSUE	ITEM	CHANGED FROM	DATE	CN. NO.	DRAFTS	CHECKER	ENG. APP.	REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL
Ø		REL TO PROD	1-6-66		RD		<i>[Signature]</i>					
A		LETTERING REPOS	17-6-66		RD		<i>[Signature]</i>					

SPECIFICATIONS
 CONNECTOR TYPE: PL-259A (UHF)
 IMPEDANCE: 51 OHMS ± 5%
 POWER RATING: 1/2 WATT

REF: A10485

MODEL	ACG 10001	PROJECT NO.	050166	ASSY. NO.		DATE	31 MAY 66
USED ON							
MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND DEVIATIONS WILL BE CAUSE FOR REJECTION REMOVE ALL BURRS AND SHARP EDGES				IF IT IS FOUND DESIRABLE TO CHANGE ANY TOLERANCE OR OTHER DETAIL SPECIFIED ON THIS DRAWING NOTIFY THE PURCHASER PROMPTLY.			
TOLERANCES							
DEC. DIM. ±		DIMENSIONS IN INCHES		SCALE		NTS	
FRAC. DIM. ±		UNLESS OTHERWISE SPECIFIED		DRILL, PUNCH, COMMERCIAL STOCK SIZES AND MANUFACTURERS		TOLERANCES ARE NOT INCLUDED.	
ANGULAR DIM. ±							

STOCK SIZE	BRASS	WEIGHT PER PC.	
MATERIAL		TYPE & TEMPER	RD
HEAT TREAT. SPEC.		SILVER PLATED	
FINISH & SPEC. NO.		DL 10008 A	

TMC (Canada) LIMITED	OTTAWA	ONTARIO
DUMMY LOAD		
DRAWN	CHECKED	MECH. DES. APP.
<i>[Signature]</i>	<i>[Signature]</i>	<i>[Signature]</i>
FINAL APPROVAL		
AUBREY		