

FX233 A

REVISIONS						
SYM	DESCRIPTION	DATE	E.M.N. NO.	DRAFT	CHKD	APPD
X1	SPEC. #12 - ADDED " & RIPPLE"	9.15.65	X1	WLA		
Ø	ORIGINAL RELEASE FOR PRODUCTION	9.17.65	Ø	R.V.V.		
A	COMPLETELY REVISED WITH CHANGES	12/9/65	15387	R.V.V.	RCB	WHH

1. TYPE: OUTER, LOWER SIDEBAND
2. DB MEASUREMENTS: ALL DB MEASUREMENTS ARE RELATIVE TO MAXIMUM SIGNAL RESPONSE IN THE PASS BAND.
3. CARRIER FREQUENCY: 243.710 KCS
4. CARRIER SUPPRESSION: AT LEAST 55 DB
5. -1DB POINTS: NOT HIGHER THAN 244.060 KCS AND NOT LOWER THAN 246.750 KCS
6. -60 DB POINTS NOT LOWER THAN 243.690 KCS AND NOT HIGHER THAN 246.960 KCS.
7. INSERTION LOSS 4DB MAX.
8. INPUT IMPEDANCE: 500 OHMS
9. OUTPUT IMPEDANCE: 500 OHMS
10. ALL SPURS AT LEAST 60 DB DOWN BETWEEN 150 KCS & 350 KCS.
11. MAXIMUM PASSBAND RIPPLE VS. TEMPERATURE:
    1 DB FROM +15°C TO +55°C
    1.5DB FROM -30°C TO +15°C
    3DB FROM -40°C TO -30°C



NOTE: CHANNEL DESIGNATION REFERS TO 250 KCS FURTHER SIDEBAND INVERSIONS MUST BE TAKEN INTO ACCOUNT IN DETERMINING THE FINAL CHANNEL DESIGNATION.

MARKING PROCESS: AS PER TMC SPECIFICATION S-727.

LETTERING: 1/8 HIGH BLACK GOTHIC, LOCATED AS SHOWN.

NOTE: UNIT HERMETICALLY SEALED.

REQ'D.	ITEM	PART NUMBER	DESCRIPTION	SYMBOL

LIST OF MATERIAL

1	CMRB -1	
Q'TY./UNIT	MODEL USED ON	ASS'Y. NO.

SCALE —H— CODE

MATERIAL —H—

FINISH —H—

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

DECIMALS .X ± .05, .XX ± .01, .XXX ± .005 — TOLERANCES — FRACTIONS ± 1/64, ANGLES ± 0° 30'

THE TECHNICAL MATERIEL CORP.
MAMARONECK, NEW YORK

TITLE: BANDPASS FILTER, CHANNEL B2

DRAWN H. AUSTIN	DATE 7-29-65	FINAL APPROVAL	DATE 9/17/65
CHECKED	DATE 9/16/65		
ELECT. DES.	DATE	FX233	A
MECH. DES.	DATE	SHEET	REV. LTR.

NOTES

THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.