



HARDWARE SUPPLIED:
 ONE HEX NUT 1/2 X 3/32
 ONE 1/2 DIA. INT. TOOTH LOCKWASHER.
 BRASS NICKEL PLATED.

REQ. PER UNIT	USED ON			RV112	Ø
	MODEL	ASS'Y. NO.	DATE		
1	GPT-10KLF		5-30-66		

SPECIFICATIONS:
 TOLERANCE: ± 5%
 TAPER: LINEAR
 MAX. AMB. TEMP: +105 °C
 MATERIAL: AS PER MIL-R-19 (RA20)
 ROTATION: 290°-305°
 TORQUE: 1 TO 12 INCH OUNCE,
 STOP TORQUE: 8 INCH POUNDS
 BACKLASH: 3° MAX.
 DIELECTRIC STRENGTH: 900 VRMS
 POWER DISSIPATION: PANEL UNIT - 2.0W MAX.
 REAR UNIT - 1.5W MAX.

							REQ. ITEM	PART NO.	F. BUDETTI	DESCRIPTION	SYMBOL		
								STOCK SIZE	THE TECHNICAL MATERIEL CORP. MAMARONECK. NEW YORK				
								MATERIAL	RESISTOR, VARIABLE, DUAL WIRE WOUND				
Ø	ORIGINAL RELEASE FOR PRODUCTION	6/14/66	CV					TYPE & TEMPER	HEAT TREAT. SPEC.	DRAWN	CHECKED	FINAL APPROVAL	
SYM	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.							
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES		SCALE											
DECIMALS .X ± .05 .XX ± .01 .XXX ± .005	TOLERANCES	FRACTIONS ± 1/64 ANGLES ± 0° 30'	CODE C	S401-106 (D43 M) S401-61 (4)									
								FINISH & SPEC. NO.	ELEC. DES. APP.	MECH. DES. APP.	RV112	Ø	