THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.

REQ. PER UNIT	USED ON MODEL	ASS'Y. NO.	DATE		
1	HFR-1/T		6-9-62	A-2484	B





SCHEMATIC

WINDING PROCEDURE

1. WIND 9 TURNS EVENLY SPACED OVER A 230° ANGLE. WIND TURNS IN THE DIRECTION SHOWN.
2. PUSH TURNS TOGETHER OR SPREAD APART AS NEEDED TO MEET INDUCTANCE SHOWN IN TEST SPECIFICATIONS.
3. BAKE FOR ½ HOUR AT 215°F. TO REMOVE MOISTURE.
4. COAT COIL & CORE WITH GL-102 (ITEM 3) AND BAKE FOR ½ HOUR @ 215°F.

* NOTE: USE TMC COIL STANDARDS FOR TEST REFERENCE.

TEST SPECIFICATIONS

INDUCTANCE = 0.45 uh ±.01 uh
WITH COIL CLAMPED INTO Q METER - ½" AWAY FROM TERMINALS WITH FINISH END TO LOW SIDE.
Cdist = 1.0 uuf (REF ONLY). Q = 180 MIN AT 25 MC
OPER. FREQ. RANGE = 25.75 - 33.75 MC

SYMBOL USED
L1052 A

	REQ.	ITEM	PART I.C	ANGAR DESCRIPTION	SYMBOL
X	3		GL-102	Q-MAX	
X	2		WI-122-22	MAGNET WIRE SINGLE #22	
1	1		CI-127-1	CORE, TOROID	

SYM	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
B	NOTE ADDED	1-12-67	17575	RME	C.D.L	
A	Q WAS 180 MIN @ 29.75 MC. WINDING WAS 10 TURNS FOR 280° Cdist ADDED, INDUCT WAS .47uh	6-7-63	9219			

STOCK SIZE

MATERIAL

TYPE & TEMPER | HEAT TREAT. SPEC.

FINISH & SPEC. NO.

THE TECHNICAL MATERIEL CORP.
MAMARONECK, NEW YORK

COIL, RF, ASSEMBLY
BAND #8 OSC.

DRAWN	CHECKED	FINAL APPROVAL
J. PINGER		A-2484 B

ELEC. DES. APP. | MECH. DES. APP.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES ON
FRAC. ± 1/64 DEC. ± .005 ANGLES ± 1/2°

SCALE:

MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION.
REMOVE ALL BURRS AND SHARP EDGES