



ELECTRICAL SPECIFICATIONS:

COIL Latch - 11,00 ohm \pm 10%
 Trip - 43 ohm \pm 10%

PILE UP 4 cs (4 P.D.T.)

CONTACTS Code 14 - 1/4 silver
 Rated 20 amperes 125 V, AC resistive.

ADJUSTMENT Latch - operate - 220V 60 cycles AC or less
 Trip - operate .155 amperes
 Non - operate .140 amperes

MOUNTING DATA:

Four 5/32" diameter holes on 1-1/2" X 1-1/4" mounting centers.

NOTE: PHYSICAL APPEARANCE OF RELAY WILL VARY DEPENDING ON VENDORS CONFIGURATION. IN ALL CASE'S ASSY WILL BE ELECTRICALY. & MECHANICALY INTERCHANGEABLE

C		NOTE ADDED	10-16-85	29093				
B	1	CLERICAL CHANGE	9.2.64	+	WB	@	DB	
A	2	Elect Specs (Coil) Latch WBS 200V	12-2-60	3621	RU	JCB	DB	
	1	Elect Specs (Coil) Latch WBS 110V						
ISSUE	ITEM	CHANGED FROM	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.	
TOLERANCES			SCALE:					
DEC. DIM. \pm			MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES					
FRAC. DIM. \pm								
ANGULAR DIM. \pm								

1	GPT-10K	AR-161	A-5843	B-24-64
REQ. PER UNIT	MODEL	PROJECT NO.	ASS'Y. NO.	DATE
USED ON				

REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
		THE TECHNICAL MATERIEL CORP. MAMARONECK. NEW YORK	
	STOCK SIZE	IPA PLATE OVL'D. RELAY ASS'Y.	
	MATERIAL		
		16	JCB
		DB	APB
	TYPE & TEMPER	HEAT TREAT. SPEC.	FINAL APPROVAL
			AR-101
	FINISH & SPEC. NO.	ELEC. DES. APP.	MECH. DES. APP.
			C