



ELECTRICAL SPECIFICATIONS:

COIL Latch - 11,00 ohm ± 10%
 Unlatch - 10,000 ohm ± 10%

PILE UP 4 C's (4 P.D.T.)

CONTACTS 1/4" Silver
 Rated 25 amperes non inductive load

ADJUSTMENT Latch operate 220 V 60 cycles AC or less
 Unlatch - 0.011 amperes or less

MOUNTING DATA:

Four 5/32" diameter holes on 1-1/2" X 1-1/4" mounting centers.

NOTE:
 PHYSICAL APPEARANCE OF RELAIS
 WILL VARY DEPENDING ON VENDORS
 CONFIGURATION. IN ALL CASE'S ASSY
 WILL BE ELECTRICALY & MECHANICALY
 INTERCHANGEABLE

C		NOTE ADD	10-17-85		GDL		
B	1	CLERICAL CHANGE	9.2.64	+	hjb	@	
A	3	Elect. Specs. (Coil) Latch was 11,000 ohm	12-2-60	3621	RJ	90%	
	2	Elect. Specs. (Coil + Adj) Unlatch was Trip					
	1	Elect. Specs. (Contacts) Rated was 20					
ISSUE	ITEM	CHANGED FROM	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.

TOLERANCES SCALE:

DEC. DIM. ± MAXIMUM ALLOWABLE TOLERANCES HAVE
 FRAC. DIM. ± BEEN DETERMINED AND ANY DEVIATIONS
 ANGULAR DIM. ± WILL BE CAUSE FOR REJECTION.
 REMOVE ALL BURRS AND SHARP EDGES

1	GPT-1DK	AR-161	A-5853	8-24-64
REQ. PER UNIT	MODEL	PROJECT NO.	ASS'Y. NO.	DATE
USED ON				

REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
		THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK	
STOCK SIZE		IPA SCREEN OVLD. RELAY ASS'Y.	
MATERIAL			
TYPE & TEMPER	HEAT TREAT. SPEC.	DRAWN	CHECKED
FINISH & SPEC. NO.		ELEC. DES. APP.	MECH. DES. APP.
		AR-107	C