



**MOUNTING ASSEMBLY**

- 1- SLIDE ITEM 4 (ITEM 2) OVER END OF WIRE.
- 2- STRIP WIRE END 3/16"
- 3- PLACE ITEM 4 (ITEM 4) ON END OF WIRE & CRIMP.
- 4- SLIDE ITEM 6 UP OVER ITEM 4. APPLY HEAT 500-750° F FOR A FEW SECONDS UNTIL ITEM 6 SHRINKS TIGHT TO ITEM 4.

**SYMBOL NOTES**

○ - DENOTES ITEM NO'S

⬡ - DENOTES LUGS

**NOTICE TO PERSONS RECEIVING THIS DRAWING**

THE TECHNICAL MATERIEL CORPORATION claims proprietary right in the material disclosed hereon. This drawing is issued in confidence for engineering information only and may not be reproduced or used to manufacture anything shown herein without permission from THE TECHNICAL MATERIEL CORPORATION to the user. This drawing is loaned for mutual assistance and is subject to recall at any time.

Property of:  
**THE TECHNICAL MATERIEL CORPORATION**  
MAMARONECK, NEW YORK

DECIMAL PT. DELETED FROM IT 5	1025.66	17050	WHO	ES	WJS		
IT. # WAS TE 197-6	328.66	16008	WJS	WJS	WJS		
ASSEMBLY NOTES DELETED, LUGS REDRAWN	1027.62	7487	WJS	WJS	WJS		
ITEM (4) WAS AN-440-4 (16) PX-6 #3-2, LREQ DELETED							
BYM	ZONE	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
UNLESS OTHERWISE SPECIFIED:			SCALE				
DIMENSIONS ARE IN INCHES			MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS & SHARP EDGES				
TOLERANCES ON FRACTIONS ± 1/64			DECIMALS ± .005		ANGLES ± 1/2°		

#	6		DELETED	
12 1/8	5	PX-100-1-750	SLEEVING, INSULATION	BLACK
6	4	TE-197-4-25	TERMINAL, LUG, INSULATED	
25"	3	HWC-6(127) B9	CABLE, INSULATION	WHITE
25"	2	HWC-6(127) B92	CABLE, INSULATION	WH/RED
25"	1	HWC-6(127) B90	CABLE, INSULATION	WH/BLK

REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK			
STOCK SIZE			
CABLE ASSEMBLY, ELECTRICAL LINE FEED PLATE TO LINE FILTER BOARD			
MATERIAL			
DRAWN: WJS, CHECKED: BUZZO, FINAL APPROVAL: WJS			
TYPE & TEMPER		HEAT TREAT. SPEC.	
ELEC. DES. APP.		MECH. DES. APP.	
FINISH & SPEC. NO.		SHEET OF	
GPT-10K		3-1-62	
REQ. PER UNIT		DATE	
USED ON		FINISH & SPEC. NO.	
ELEC. DES. APP.		MECH. DES. APP.	
SHEET OF		CA-679	

CA-679 C