



**NOTE:**  
 1- SUGGESTED DISTANCE FROM WALL FOR VENTING PURPOSES AND ACCESS TO FILTER DOOR APPROX. 12 INCHES  
 2- IF ONLY 4 BOTTOM SHOCK ISOLATORS ARE USED DISREGARD TOP HOLES

**ACCESSORY MOUNTING HOLES**  
 a- MODEL TAC-1  
 b- MODEL ATS-MCU  
 c- MODEL ATS-CU  
 d- MODEL TRL

REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL
6	6	FW62HBN	WASHER, FLAT	
6	5	LWS 62 MSN	LOCKWASHER SPRING TYPE	
2	4	SCHH6211SN24	BOLT, HEX HEAD	
4	3	SCHH6211SN16	BOLT, HEX HEAD	
1	2	MS-1389-20.00	GROUND STRAP	
6	1	SH-100	SHOCK ISOLATOR	

REQ. ITEM		PART NO.	DESCRIPTION	SYMBOL
<b>THE TECHNICAL MATERIEL CORP.</b> MAMARONECK, NEW YORK				
<b>SHOCK MOUNTING INSTALLATION</b> FOR GPT-750(-)2				
DRAWN		CHECKED		FINAL APPROVAL
TYPE & TEMPER		HEAT TREAT. SPEC.		
FINISH & SPEC. NO.		ELEC. DES. APP.		MECH. DES. APP.
		SHEET		OF

SYM	ZONE	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
UNLESS OTHERWISE SPECIFIED:							
DIMENSIONS ARE IN INCHES							
TOLERANCES ON							
FRACTIONS ± 1/64		DECIMALS ± .005		ANGLES ± 1/2°			
SCALE			MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS & SHARP EDGES				

REQ. PER UNIT	MODEL	SECTION	ASS'Y. NO.	DATE
	GPT-750(-)2			4-15-63