IF IT IS FOUND DESIRABLE TO CHANGE ANY TOLERANCE OR OTHER DETAIL SPECIFIED ON THIS DRAWING NOTIFY THE PURCHASER PROMPTLY.

MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES

TMC PART NO.	"A" HOLES	CUTOUT
MS 1648	NONE	NONE
MS 1648-2	9	1



MATL: 20 GA. ST'L
2 - REQ.
FLANGED PIPE



Section B-B



HINGE PIN NOTE
PIN B 1/8 SHORTER THAN PIN A
PIN C " " " " B



MAT'L: 3/32 THICK FORMED ST'L.

FINISH NOTE:
DEGREASE & PREPARE SURFACE FOR FOLLOWING:
3114 - ZINC CHROMATE PRIMER
5220 - RCAF BLUE GREY
or Prime and Paint Per Customer Specifications.

HOLE LEGEND:
A = 11/64 DIA (9 REQ.)

HINGE - 2" MIN STL
7/8 LEAF
5/32 MIN STL PIN

SUITABLE GASKET TO BE ATTACHED TO OUTSIDE SURFACE OF 1" RETURN
SEE SECTION "B-B"

SEC A-A

ISSUE	ITEM	CHANGED FROM	DATE	CN. NO.	DRAFTS	CHECKER	ENG. APP.
G		PART NO. CHART CUTOUT & "A" HOLES ADDED	8/27/60	19530	[illegible]	Dee	FB
F	3	(6) .073 D. Holes added	6/9/60	5010	DRM	DEE	FB
	2	(2) 6-32 Tap Item Brkt rotated 90°					
	1	Door latch Brkt rotated 90°					
E	1	DIM. 22 1/32 was 22 3/8	3/27/60	4517	DRM	DEE	FB
D	2	Finishes T&E Deleted Under Finish Added Per Cust. Spec.	12/9/59	2374	DRM	DEE	FB
C		DIM. CHG. 22 3/8 WAS 22 1/2 & F LATCH & ROD HOLES WERE REFERENCED FROM OPP.	9/28/59	1325	ABC		
B		ADDED -2 F-2 (FINISH CHART ADDED)	8/25/59	1225	ABC	Dee	FB
A	2	Section B-B Added	6/4/59		J.C.B	Dee	FB
	1	Note Added					

TOLERANCES

ALL OTHERS: DEC. DIM. ± AS NOTED; FRAC. DIM. ± 1/64; ANGULAR DIM. ±

SCALE:

DRILL, PUNCH, COMMERCIAL STOCK SIZES AND MANUFACTURERS TOLERANCES ARE NOT INCLUDED.

FORM—111

REQ PER UNIT	MODEL	PROJECT NO.	ASS'Y. NO.	DATE
1	SPT-10K	AX-166		12-4-58

USED ON

REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL
22 TO 20 GA.			THE TECHNICAL MATERIEL CORP. MAMARONECK. NEW YORK	
STOCK SIZE				
STEEL			DOOR, REAR RIGHT	
MATERIAL		WEIGHT PER PC.		
TYPE & TEMPER				
HEAT TREAT. SPEC.			DRAWN: 8-13-59	ELEC. DES. APP.	MECH. DES. APP.
FINISH & SPEC. NO.			CHECKED	FINAL APPROVAL

HA-114-1
PM-531-A-36.56
REF. PO-186-1

REF. B-1391 MS-1648 G

MS-1648 G