



A ~ 1/4 (.250) DIA. 4 REQ.

NOTE:
USE MATERIAL THICKNESS FOR MAX. RADIUS ON ALL BENDS UNLESS OTHERWISE SPECIFIED.

D	B2	BLANK SIZE REF: MS-1784-7, DELETED	4-25-63	8912	MS	MS	MS
C	H6	DIM. 16 1/4 WAS 16 3/8 DIM. 16 7/8 WAS 17	10-17-60	3219	MS	MS	MS
B	H6	7" NOTCH WAS 1" NOTCH	9-28-60	3099	CU	MS	MS
A	B2	REF. BLANK SIZE MS-1784-7 ADDED	8-31-60	11	MS	MS	MS
ISSUE ZONE		DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
TOLERANCES			SCALE:				
DEC. DIM. ±			MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION.				
FRAC. DIM. ± 1/64			REMOVE ALL BURRS AND SHARP EDGES				
ANGULAR DIM. ±							

1	DVM-4			2-1-62
1	DVM-2			7-22-60
REQ PER UNIT	MODEL	SECTION	ASSY. NO.	DATE

4	2	FS-110-1	STUD, SLOTTED HEAD	
4	1	FS-109-3	RING, STUD RETAINING	
REQ. ITEM	PART NO.		DESCRIPTION	SYMBOL
.051			THE TECHNICAL MATERIEL CORP.	
STOCK SIZE			MAMARONECK. NEW YORK	
ALUMINUM, PERF.			TOP COVER	
MATERIAL			MODEL DVM-2	
5052-H32			DRAWN	
TYPE & TEMPER			ELEC. DES. APP.	
HEAT TREAT. SPEC.			MECH. DES. APP.	
5404-YEL. IRIDITE			CHECKED	
FINISH & SPEC. NO.			FINAL APPROVAL	
			MS-2328	
			D	