

USE MATERIAL THICKNESS FOR MAX. RADIUS ON ALL BENDS UNLESS OTHERWISE SPECIFIED

MOUNT INSERTS AFTER FINISHING

MS-2917 D

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

TOLERANCES: DECIMALS .X ± .05, .XX ± .01, .XXX ± .005; FRACTIONS ± 1/64; ANGLES ± 0° 30'

SYM	ZONE	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
D	C9	ADDED (1) "J" HOLE	7-31-63	9671	AK	JMK	WRP
C	C-	(7) "D" HOLES RELOCATED	2-19-63	8251	EC	WRP	WRP
B	F2	(1) "H" DETAIL WAS (1) 2" DIA. HOLE	10-30-62	7586	EC	WRP	WRP
A	F2	(1) "D" HOLE DELETED, (1) "H" HOLE ADDED	10-24-62	7489	EC	WRP	WRP

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES ON
FRACTIONS ± 1/64 DECIMALS ± .005 ANGLES ± 1/2°

SCALE

MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS & SHARP EDGES

TMC FORM NO. 111

REQ. PER UNIT	MODEL	SECTION	ASS'Y. NO.	DATE
1	HFR-1/0			7-24-62

USED ON

REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL
5	1	NT-129-832-4	NUT, ROUND, SWAGE TYPE	B
		.081	GELLMAN	
		STOCK SIZE	THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK	
		ALUMINUM	PLATE, LEFT SIDE	
		MATERIAL		
		5052-H32	V.R.R.	
		TYPE & TEMPER / HEAT TREAT. SPEC.	DRAWN / CHECKED / FINAL APPROVAL	
		5404 YEL IRIDITE	MS-2917 D	
		FINISH & SPEC. NO.	ELEC. DES. APP. / MECH. DES. APP. / SHEET OF	

DEFIANCE NO. 1020