



LEGEND

HOLE	DESCRIPTION	REQ.
A	3/16 DIA.	2
B	1/64 DIA.	6
C	.161-.164 DIA.	4

UNLESS OTHERWISE SPECIFIED:

1. USE MATERIAL THICKNESS FOR MAXIMUM RADIUS ON ALL BENDS.
2. ALL ANGULAR BENDS 90°.
3. REMOVE ALL BURRS AND SHARP EDGES.
4. MOUNT INSERTS AFTER FINISHING.

UNLESS OTHERWISE SPECIFIED ~

- 1- USE MATERIAL THICKNESS FOR MAX RADIUS ON ALL BENDS.
- 2- ALL BENDS 90°.
- 3- MOUNT INSERTS AFTER FINISHING.

1	2	NT-129-440-4	NUT, ROUND, SWAGE TYPE	C
4	1	NT-129-440-4	NUT, ROUND, SWAGE TYPE	C
REQ. ITEM	PART NO.		DESCRIPTION	SYMBOL
1/16 THICK		THE TECHNICAL MATERIEL CORP.		
STOCK SIZE		MAMARONECK, NEW YORK		
ALUMINUM		SUPPORT, MODULE GUIDE, FRONT		
MATERIAL				
5052 H32	—			
TYPE & TEMPER	HEAT TREAT. SPEC.			
S404-IRIDITE 14-2 AL-COAT	ELEC. DES. APP. MECH. DES. APP. SHEET OF			
FINISH & SPEC. NO.		MS-3571		

SYM	ZONE	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
UNLESS OTHERWISE SPECIFIED:							
DIMENSIONS ARE IN INCHES			SCALE FULL CODE A				
TOLERANCES ON FRACTIONS ± 1/64			DECIMALS ± .005			ANGLES ± 1/2°	
MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS & SHARP EDGES							

REQ. PER UNIT	MODEL	SECTION	ASS'Y. NO.	DATE
1	MNF-1			4-29-63
USED ON				