ZONE	REVISIONS					
	LTR	DESCRIPTION	DATE	E.N.R. NO.	DRAFT	CHKD	APPD
	X1	"A" HOLE REQ'D WAS (32) ; ADDED "D" HOLES & ITEM-1	5/3/65		JL	J.M.	W.J.
C108 C184	X2	4 7/8 WAS 4 15/16 6 3/16 WAS 6 1/4 1 3/4 WAS 1 13/16	5/11/65	X2			W.J.
C4	X3	4-7/8 DIM WAS 5 1/4	5/18/65	X3			
	Ø	ORIGINAL RELEASE FOR PRODUCTION	5/18/65	M		J.M.	
A2 E4	A	TE108-29 DELETED (REF "B" HOLES) CHANGED TO "A" HOLES "D" HOLES DIM ADDED	8/11/65	14547	RVV		

HOLE	DESCRIPTION	REQ
A	11/64 DIA	32
B	9/64 DIA	16
C	7/64 DIA	6

UNLESS OTHERWISE SPECIFIED:

1. USE MATERIAL THICKNESS FOR MAXIMUM RADIUS ON ALL BENDS
2. ALL ANGULAR BENDS 90 DEGREES
3. REMOVE ALL BURRS AND SHARP EDGES
4. MOUNT INSERTS AFTER FINISHING

MOUNT IN ALL "A" HOLES (1)

OPPOSITE SIDE IDENTICAL

LOCATING BASE LINES

METAL STAMP TMC P/N WITH LATEST REV. LETTER.

MS4582-

REF: LD1897

REQ'D.	ITEM	PART NUMBER	DESCRIPTION	SYMBOL
			F. EATON LIST OF MATERIAL	
MATERIAL .062; ALUMINUM 5052-H32			THE TECHNICAL MATERIEL CORP. MAMARONECK. NEW YORK	
FINISH 5404-YEL. IRIDITE			TITLE CHASSIS, ELECTRICAL, MAIN (RGCB-1)	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES			DRAWN E. Jensen DATE 5/2/65	FINAL APPROVAL F. Eaton DATE 5/11/65
DECIMALS X ± .05 XX ± .01 XXX ± .005 TOLERANCES FRACTIONS ± 1/64 ANGLES ± 0° 30'			CHECKED DATE 5/11/65	
			ELECT. DES. DATE 5/11-65	MS4582 A
			MECH. DES. W. JORDAN DATE 5/9/65	SHEET REV. LTR.

STANPAT CO. WHITESTONE, N.Y. U.S.A.